

## SUPERIOR F 900 series

Build-in manual bio-fireplace



EU CLASS  
NORM



ECO & SAFE  
BEST FOR YOU



100%  
ORIGINAL  
by BIOPASJA

VBSB F 900



### SAFE CONTROL

A thoughtfully designed safety chamber offers peace of mind by providing thermal insulation and ensuring any spilled bioethanol remains safely outside the combustion area. Handy indicators make bioethanol measurement a breeze.

### ECO HEATER

Experience cleaner, more mesmerizing flames with our unique V-shaped tank and catalyst insert. Adjust the flames effortlessly with a safety-first cold handle.

### Warranty

All Bio-fireplaces undergo a thorough quality control process, which includes a leak test to ensure their safety and performance.

**Manufactured and tested according European Standard EU norm EN 16647 Predicate to test report no. 3515 A1 21**

*Note: All calculations and figures presented are based on controlled testing and should be considered as theoretical*

Discover a Fireplace that Offers Six Unique Configurations in one unit.

Introducing Biopasja's **SUPERIOR** Series: The Peak of Bio-fireplace Innovation. Immerse yourself in an exceptional world of luxury and adaptability with the **SUPERIOR** Bio-fireplace from Biopasja. It's not just a fireplace; it's a versatile design element that effortlessly blends with your interior preferences.

**Single-Sided** Simplicity: This finely crafted fireplace seamlessly combines classic aesthetics with functionality. Built with premium 2mm steel and a sleek black powder-coated finish, it offers easy installation, crystal-clear viewing through 10mm Optiwhite glass, and a choice of Artflame 700 burner or Dimplex vapor unit. Elevate your space with optional features like a log set tray and a 6mm black reflecting glass. Enjoy the perfect blend of style and warmth with this exceptional bio-fireplace.

| MODEL  | FRONT SIDED                          |
|--|--------------------------------------|
| Dimensions without profile edges in mm (L x D* x H)<br>D+ 10 mm upper heat deflector edge - *D: 310mm<br>(D+10) + 18 mm surrounding mounting edges - *D: 328mm | 900x300x494<br>+ 10mm<br>+ 18mm      |
| Burner options:<br>A - Artflame 700 black<br>B - Dimplex water vapor unit  | A & B                                |
| A - Artflame burner tank capacity<br>B - Dimplex water reservoir   | A - 2,8L<br>B - 1,3L                 |
| (ARTFLAME) Flame control   | Manual stainless cold handle         |
| (ARTFLAME) Amount of ethanol combusted at maximum opening /hour  | 0.46 L/h                             |
| (ARTFLAME) Maximum heat at maximum opening/hour kW/h or BTU/h  | 2,7 kW/h or 9100 BTU/h               |
| (ARTFLAME) Net weight without bioethanol   | 14,0 kg                              |
| (ARTFLAME) Required air venting grid, in cm <sup>2</sup> (100cm <sup>2</sup> x 2,7 kW)   | 270 cm <sup>2</sup>                  |
| (ARTFLAME) Operating airflow rate, factor 99.4 Nm <sup>3</sup> /h / 0.1L/h   | 45,7 Nm <sup>3</sup> /h/0,46L/h*     |
| Minimal room size m <sup>3</sup> (desired temp. increase with 5°C) & heating area capacity 0,1kW per 1m <sup>2</sup> for well-insulated space                  | 54 m <sup>3</sup> & 27m <sup>2</sup> |

*\* Nm<sup>3</sup> stands for m<sup>3</sup> of gas in normal conditions (101235 Pa) The value includes the moisture content of ambient air 50% relative humidity Rh*

- Superior bio-fireplace made of DC01, 2mm steel, powder coated rough black (RAL9005).
- Upper heat deflector edge profile + 10mm front (28mm)
- Surrounding mounting edge profile + 18mm front.
- Glass holder Easy-simple slider Pro U04.
- Transparent tempered Optiwhite glass 10mm.
- BURNER: Artflame 700 burner or Dimplex vapor unit.
- OPTIONAL log set tray.
- OPTIONAL vertical 6mm reflecting stove painted wall glass panel.
- Cut out for support vertical reflecting glass wall panel.

