

LYKKE

Free-standing manual bio-fireplace

ECO & SAFE
BEST FOR YOU




EU CLASS
NORM



100%
ORIGINAL
by BIOPASJA

LYKKE



LYKKE Free-Standing Bio-Fireplace.

Elevate your living space with the LYKKE Bio-Fireplace, a symbol of modern luxury and clean design. Constructed from sturdy 10mm Optiwhite glass, this fireplace is built to last and adds a touch of sophistication to any room. It features a high-quality Artflame 900 burner, available in stainless steel or black, which provides consistent, smoke-free flames for up to 6 hours. Perfect as a room divider or a central decor piece, the LYKKE bio-fireplace blends seamlessly into contemporary settings, offering style and warmth in a compact, free-standing design.

SAFE CONTROL

A thoughtfully designed safety chamber offers peace of mind by providing thermal insulation and ensuring any spilled bioethanol remains safely outside the combustion area. Handy indicators make bioethanol measurement a breeze.

ECO HEATER

Experience cleaner, more mesmerizing flames with our unique V-shaped tank and catalyst insert. Adjust the flames effortlessly with a safety-first cold handle.

Warranty

All Bio-fireplaces undergo a thorough quality control process, which includes a leak test to ensure their safety and performance.

Manufactured and tested according to European Standard
EU norm EN 16647 Predicate to test report no. 3515 A1 21

Note: All calculations and figures presented are based on controlled testing and should be considered as theoretical

MODEL	LYKKE
Dimensions without profile edges in mm (L x D x H)	1200x350x900
Burner options: Artflame 900 stainless or black glossy enamel RAL 9017	Stainless or black
Artflame 900 burner tank capacity	3,6L
(ARTFLAME) Flame control	Manual stainless cold handle
(ARTFLAME) Amount of ethanol combusted at maximum opening /hour	0.6 L/h
Combustion time	up to 6 h
(ARTFLAME) Maximum heat at maximum opening/hour kW/h or BTU/h	3,5 kW/h or 12000 BTU/h
Calorific value of fuel /with consumption of 1 L bioethanol (7,4 kW/kg x 0,789 kg/L = 5,839kW/L & 19,920 BTU/L)	5,839 kW/L & 19,920 BTU/L
(ARTFLAME) Net weight without bioethanol	58,0 kg
Minimal room size m ³ (desired temp. increase with 5°C) & heating area capacity 0,1kW per 1m ² for well-insulated space	70 m ³ & 35m ²

** Nm³ stands for m³ of gas in normal conditions (101235 Pa) The value includes the moisture content of ambient air 50% relative humidity Rh*

1. Transparent tempered Optiwhite glass 10mm
2. Patented invisible glass holder concealed latches neo pro
3. Magnetic transparent tempered Optiwhite glass 10mm with
4. Steel recess powder coat rough black RAL9005
5. BURNER: Artflame 900 burner with stainless or black finish

